





FLEX-FLYTE® VF

TEMPERATURE RANGE



DIAMETER RANGE



CONSTRUCTION

Single ply flame retardant vinyl coated fiberglass

APPLICATIONS

- ▶ Air (/products-search#air)
- ▶ Chemical Fumes (/products-search#!chemical-fumes)
- ▶ Dust (/products-search#!dust)
- ▶ Exhaust + Ventilation (/products-search#!exhaust-ventilation)

STANDARD COLORS

Smoke Grey

INDUSTRIES

- Fans (/products-search#!fans)
- Hospitals (/products-search#!hospitals)
- Marine Industry (/products-search#!marine-industry)
- Railroads (/products-search#!railroads)

STANDARD LENGTHS

25'

DETAILS

- ▶ Ideal for transfer of low volume cool and warm air
- ▶ Flame retardant to UL94V-0
- ▶ Excellent flexibility
- ▶ Great for ventilation of photo reproduction machines and fine dust collection systems

FEATURES

Fume Removal (/products-search#fume-removal)

Self-extinguishing (/products-search#!self-

extinguishing)

UV / Ozone Resistant (/products-search#!uv-

ozone-resistant)

[INQUIRE ABOUT THIS PRODUCT \(CONTACT-HI-TECH-DURAVENT\)](#)

- [ABOUT \(/ABOUT-HI-TECH-DURAVENT\)](#)
- [CORE PRODUCTS \(/CORE-PRODUCTS\)](#)
- [PRODUCTS \(/PRODUCTS\)](#)
- [REGULATORY \(/REGULATORY\)](#)
- [FAQ \(/DURAVENT-HOSE-FAQ\)](#)
- [CONTACT \(/CONTACT-HI-TECH-DURAVENT\)](#)



Flexible
Technologies



(<http://www.titeflex.com/>) (<http://www.flexibletechnologies.com/>) (<http://www.hitechmedical.net/>) (<http://www.flexibleductingmalaysia.com/>) ([http://flexschlauch-](http://flexschlauch-produktion.de/)